		26 - 18 - 17 - 17 - 17 - 17 - 17 - 17 - 17					
Section	n V-B - FM	BROADCAST	ENGINEERING	DATA	File No. ASB Referra		
Name of A	pplicant	Janice M. S	cantland		Referred by	<u> </u>	
Call letters	lif issued)		Is this apwindow?	plication bein	g filed in res	ponse to a	X Yes
			If Yes, spe	cify closing	date:	January 15, 19	992
urpose of	Application: lek	ock appropriate	bes(es))				
X Con	struct a new (main) facility		Con	struct a new	auxiliary facility	
Mod faci	lify existing ∝	onstruction per	mit for main		lify existing	construction perm	it for auxiliary
☐ Mod	lify licensed m	ain facility		Mod	lify licensed	auxiliary facility	
	s to modify, in	dicate below th	e nature of cha	nge(s) and sp	ecify the file	number(s) of the	authorizations
ffected. 	enna supportin	g-structure hel	ight	Erro	ctive radiate	i power	
Ant	enna height ab	ove average te	errain	Prec	luency		
Ant	enna location			Clas	•		
☐ Mati	n Studio locatio	n		Othe	or (Summarize b.	rioflu)	
File Num	ber(s)					· · · · · · · · · · · · · · · · · · ·	<u></u>
Allocation:		Principal	community to l	a servet		Class Ichock on	ly one box below?
Allocation:		Principal	community to l	pe served:	State		ly one box below!
Allocation:	a		County	oe served:	State OH		· — —
Allocation: Channel No. 282A Exact locat Specify as landmark.	City Rich Rich City Rich City Rich City Rich City Rich	wood L unty and state aware County	County Un If no address, sp	nion pecify distance Delaware (oH and bearing	X A C2 C2 C2 C2 C2 C2 C3 C4	B1 B C
Allocation: Channel No. 282A Exact locat Specify a landmark Geograph of array.	City Rich cion of antenne ddress, city, cor 21970 Del	wood unty and state aware County (to nearest se	If no address, spy Line Road, scond). If mountetion. Specify Sou	nion cecify distance Delaware (OH county, Oh	C2 C2 C2 C2 C2 C3 C4	B1 B C C1 C nearest town or
282A Exact locat Specify a landmark Geograph of array. North Lati	City Rich cion of antenne ddress, city, cor 21970 Del	wood unty and state. aware County s (to nearest se	If no address, spy Line Road, scond). If mountetion. Specify Sou	nion cecify distance Delaware (OH county, Oh	C2 C	B1 B C C1 C nearest town or
Allocation: Channel No. 282A Exact locate Specify as landmark. Geographs of array. North Latitude	City Rich City Continue	wood unty and state aware County (to nearest selfy tower local Longitude will	If no address, spy Line Road, scond). If mounted the presumed.	nion Delaware (ed on element) th Latitude (Longitude	OH co and bearing County, Ohit of an AM are East Longitudes	C2 C	B1 B C1 C C nearest town or linates of cente able; otherwise,
Allocation: Channel No. 282A Exact locat Specify a landmark Geograph of array. North Lati attitude s the suppo	City Rich City Rich City Rich City Rich City Rich City Rich All City Rich All City Rich City Rich Rich All City Rich Rich Rich All City Rich Rich Rich Rich Rich Rich Rich Rich	wood unty and state aware County (to nearest selfy tower local Longitude will	If no address, spy Line Road, scond). If mounts tion. Specify South presumed.	nion Delaware (ed on element) th Latitude (Longitude	OH co and bearing County, Ohit of an AM are East Longitudes	C2 C	B1 B C C1 C nearest town or linates of center able; otherwise,

SECTION V-B - FM BROADCAST ENGINEERING DATA (Page 2)

4. Does the application propose if Yes, list old coordinates.	to correct previous site coord	dinates?		Yes X N		
Latitude	, ,	Longitude o	•			
5. Has the FAA been notified of If Yes, give date and office determination, if available.		attach as an Exhibit a copy of	FAA	X Yes N		
Date December 5, 19	991 Office where filed	Great Lakes Region	•			
6. List all landing areas within nearest runway.	18 km of antenna site. Specif	y distance and bearing from	structure to	nearest point of		
Landing Area	Dis	tance (km)	Bearing (d	egrees True)		
(a) Packer, Ohio	8.8	Kn	14 Deg.	True		
						
7. (a) Elevation: Its the nearest so	eter)					
(1) of site above mean see	level;		286	meters		
	(2) of the top of supporting structure above ground (including antenna, all other appurtenances, and lighting, if any); and					
(6) of the top of supporting	ng structure above mean sea	level [(a)(1) + (a)(2)]	390	meters		
(b) Height of radiation center.	(to the nearest meter) H = H	orizontal; V - Vertical				
(1) above ground			97	meters (
			97	meters (
(2) above mean sea level.	[(aX1) + (bX1)]		383*	meters (1		
			383	meters (\		
(S) above average terrain			100	meters (I		
* Exact value 383.3 m	Exact value 383.3 m					
Attach as an Exhibit sketch(es) in Question 7 above, except it specify heights and orientation	em 7(b)(3). If mounted on an	AM directional-array element,		Exhibit No.		
Effective Radiated Power:						
(a) ERP in the horizontal plan-	e 3	kw (H*) 3 kw ((V*)			
(b) Is beam tilt proposed?				Yes X No		
If Yes specify maximum E vertical elevational plot of		beam, and attach as an Exhibi kw (H*) kw (L	Exhibit No. DNA		
*Polarization		AW (• • •			

SECTION V-B - FM BROADCAST ENGINEERING DATA (Page 3)

	10. Is a directional antenna proposed?	Yes X No
	If Yes, attach as an Exhibit a statement with all data specified in 47 C.F.R. Section 73.316, including plot(s) and tabulations of the relative field.	Exhibit No.
	11. Will the proposed facility satisfy the requirements of 47 C.P.R. Sections 73.315(a) and (b)?	Yes No
	If No, attach as an Exhibit a request for waiver and justification therefor, including amounts and percentages of population and area that will not receive 8.16 mV/m service.	Exhibit No.
	12. Will the main studio be within the protected 3.18 mV/m field strength contour of this proposal?	X Yes No
-	if No, attach as an Exhibit Justification pursuant to 47 C.F.R. Section 73.1125.	Exhibit No. DNA
	13. (a) Does the proposed facility satisfy the requirements of 47 C.F.R. Section 73.207?	X Yes No
,	(b) If the answer to (a) is No, does 47 C.F.R. Section 73.213 apply?	Yes No
	(c) If the answer to (b) is Yes, attach as an Exhibit a justification, including a summary of previous waivers.	Exhibit No. DNA
	(d) If the answer to (a) is No and the answer to (b) is No, attach as an Exhibit a statement	Exhibit No.
·		
i		
τ	<u></u> •	
<u>. 1</u>		

15. Attach as an Exhibit a 75 minute series U.S. Geological Survey topographic quadrangle map that shows clearly, legibly, and accurately, the location of the proposed transmitting antenna. This map must comply with the requirements set forth in instruction V. The map must further clearly and legibly display the original printed contour lines and data as well as latitude and longitude markings, and must bear a scale of distance in kilometers.	Exhibit No.
16. Attach as an Exhibit (ness the secret) a map which shows clearly, legibly, and accurately, and with the original printed latitude and longitude markings and a scale of distance in kilometers:	Exhibit Na.
(a) the proposed transmitter location, and the radials along which profile graphs have been prepared;	
(b) the 3.18 mV/m and 1 mV/m predicted contours; and	
(c) the legal boundaries of the principal community to be served.	
17. Specify area in square kilometers (I sq. mi 259 sq. km) and population (latest census) within the predicted 1 mV/m contour.	
Area 1,815 sq. km. Population 67,549	•
18. For an application involving an auxiliary facility only, attach as an Exhibit a map (Sectional Appenentical thank or equivalent) that shows clearly, legibly, and accurately, and with latitude and longitude markings and a scale of distance in kilometers: (a) the proposed auxiliary 1 mV/m contour; and	Exhibit No.
(b) the 1 mV/m contour of the licensed main facility for which the applied-for facility will be auxiliary. Also specify the file number of the license.	
3. Terrain and coverage data its be colculated in occordence with 47 C.F.R. Section 73.3131	
Source of terrain data: (check only one bes below)	
Linearly interpolated 30-second database 75 minute topographic map	
(Source:	
X Other (briefly supportse)	
Defense Mapping Agency (DMA) 3 arc second terrain database.	
DNA - Does not apply.	

37	Height of radiation center above average	Predicted Distances					
Radial bearing (degrees True)	elevation of radial from 8 to 16 km (meters)	To the 3.16 mV/m contour (kilometers)	To the 1 mV/m contour (kilometers)				
336.4	109.0	14.1	25.2				
0	109.3	14.1	25.2				
45	109.3	14.1	25.2				
90	109•3	14.1	25.2				
135	108-7	14.0	25.2				
180	96-0	13.2	23.8				
225	84.1	12.4	22.3				
270	86.0	12.5	22.5				
315	97.2	13.3	23.9				

^{*}Radial through principal community, if not one of the major radials. This radial should NOT be included in the calculation of HAAT.

Would a Commission grant of this application come within Section 1.307 of the FCC Rules, such Yes X No that it may have a significant environmental impact?

If you answer Yes, submit as an Exhibit an Environmental Assessment required by Section 1.331. Exhibit No.

If No. Axplain briefly why not See Engineering Statement

ENGINEERING REPORT

SILLIMAN AND SILLIMAN

8601 GEORGIA AVENUE

CONSULTING ENGINEERS

SILVER SPRING, MD 20910

20RICH03.T

Janice M. Scantland Richwood, Ohio

ENGINEERING STATEMENT

Robert M. Silliman is a Registered Professional Engineer in the State of Maryland, the District of Columbia and the Commonwealth of

ENGINEERING REPORT

SILLIMAN AND SILLIMAN

8601 GEORGIA AVENUE

CONSULTING ENGINEERS

SILVER SPRING, MD 20910

Janice M. Scantland Richwood, Ohio

ENGINEERING STATEMENT (CONT'D)

Paragraph 20.

From Appendix II it is seen that there are no other FM, TV or AM stations close enough to contribute to the radiofrequency radiation level in the vicinity of the tower. The proposal is for 3 kW ERP. However, it is anticipated that the assignment might at some later date be increased to 6 kW. Hence, the EMR study has been based on 6 kW.

The proposed radiation center is 97 meters above ground. The antenna will be of "best" case as contained in OST Bulletin No. 65 Table 1 on page 37 of this document. It is seen that with a 4 bay antenna and 10 kw of power even with a "worst" case antenna the required height above ground to meet the 1000 microwatt per Sq. Cm. requirement is 18.3 meters. Hence, even with a "worst" case antenna and 6 kW the EMR level at the base of the tower would be as follows:


EMR = $6/10x(18.3/97)^2x1000=21.4$ microwatts per Sq. Cm. which is only 2.1 percent of the guideline.

With a "best" case antenna the level would be

EMR = $6/10x(5.3/97)^2x1000=1.8$ microwatts per Sq. Cm. which is only 0.2 percent of the guideline.

Since the proposed site is in a rural area, the only workers who will be permitted to approach the tower base will be radio technicians. A sign will be posted on the tower cautioning of radio frequency radiation hazard if the tower is climbed with the transmitter in operation. The permittee has adopted the policy that, when it is necessary to climb the tower, the transmitter will be shut off while a climber is on the tower.

The proposed site is not located in a restricted area and its proposed operation will be in compliance with the RF protection guidelines for humans located near the antenna supporting structure. Hence, by definition in Section 1.1306 of the FCC Rules, this proposal is deemed to have no significant effect on the quality of the human environment and is



JANICE M. SCANTLAND RICHWOOD, OHIO

APPENDIX 1

Silliman & Silliman

Date: 12/05/91

Study Name : FM STUDY FOR CH 282A AT RICHWOOD, OHIO

Channel : 282A

Coordinates: N 40 19 46.0 W 83 14 39.0 Separations: FM Zone 1 - Commercial


Call	City &	State Stat	File - number	Chan	ERP	HAAT	Zn Latitude	Longitude	Bear	Dist	Req'd	Clear	Note
										k	ilomete	rs	
	BOWLING GREEN	OH LIC	BLH 900925KC	228A	4.10	397	1 41 27 28.0	83 39 33.0	344.6	130.09	10.0	120.09	
Korn	MIAMISBURG	OH LIC	BLH 870514KA	229B	50.0	492	1 39 39 36.0	84 18 50.0	231.1	117.78	15.0	102.78	
WQIO	MOUNT VERNON	OH LIC	BLH 870625KB	229B	37.0	563	1 40 24 18.0	82 26 20.0	82.7	68.91	15.0	53.91	
WITFFM	TIFFIN	OH LIC	BLH 850715KW	279B	50.0	430	1 41 8 20.0	83 14 45.0	359.9	89.89	69.0	20.89	
WYMJFM	BEAVERCREEK	OH LIC	BLH 841029CB	280A	1.15	522	1 39 44 12.0	84 9 25.0	230.0	101.99	31.0	70.99	
WLBCFM	MUNCIE	IN LIC	BLH 5019	281B	50.0	420	1 40 9 38.0	85 22 42.0	264.8	182.56	113.0	69.56	
HQAL	CLEVELAND	OH LIC	BLH 860219KB	281B	11.0	1060	1 41 22 45.3	81 43 12.0	47.2	173.52	113.0	60.52	
WQAL	CLEVELAND	OR CP	BPH 910826IB	281B	11.0	1060	1 41 22 45.0	81 43 12.0	47.2	173.51	113.0	60.51	
WPAYFM	PORTSMOUTH	OH LIC	BLH 890612KC	281C	100	1000	2 38 43 20.0	83 0 5.0	173.3	179.66	165.0	14.66	CLOSE
WOMC	DETROIT	MI LIC	BLH 6899	282B	190	360	1 42 28 25.0	83 6 56.0	2.5	238.37	178.0	60.37	
WELA	EAST LIVERPOOL	OR LIC	BLH 790529AB	282B	50.0	330	1 40 37 48.0	80 36 10.0	80.6	226.45	178.0	48.45	
WELA	EAST_LIVERPOOL	OF APP	RPH 900626TC	282B	50.0	492	1 40 37 48.0	80 36 10.0	80.6	226.45	178.0	48.45	

JANICE M.SCANTLAND RICHWOOD, OHIO

APPENDIX II

Silliman and Silliman Silver Spring. MD

December 4. 1991



ENGINEERING REPORT

SILLIMAN AND SILLIMAN

8601 GEORGIA AVENUE

CONSULTING ENGINEERS

SILVER SPRING, MD 20910

Janice M. Scantland Richwood, Ohio

AFFIDAVIT

ROBERT M. SILLIMAN, being duly sworn upon oath deposes and says:

That his qualifications are a matter of record with the Federal Communications Commission;

That he is a registered professional engineer in Maryland, the District of Columbia and the Commonwealth of Virginia and is a partner in the firm of Silliman and Silliman:

That this firm has been retained by Janice M. Scantland to prepare this engineering statement;

That he has either prepared or directly supervised the preparation of all technical information contained in this engineering statement and that the facts stated in this engineering statement are true of his knowledge except as to such statements as are herein stated to be on information and belief and as to such statements he believes them to be true.

obert M. Silliman

Subscribed and sworn to before me this 5th day of December 1991.

Cathy A Ozdany Notary Public

My Commission expires April 1, 1994.

(SEAL)

